

Data Sheet

Fujitsu PRIMERGY BX922 S2 Dual-Socket Server Blade

Future-oriented Server Blade with all the prerequisites for virtualization environments

The PRIMERGY BX Blade Servers are the ideal choice for data center solutions of today and tomorrow. Our blade servers provide maximum performance and maximum redundancy, but with only minimum space requirements, low power consumption and a reduction in the time and effort required for cabling. The PRIMERGY BX system family is designed to share components between chassis in order to react quickly and easily to changing business requirements. Storage and server blades can be added without any extra effort, as would be needed when cabling or adding management software. You can use the same applications, rely on the same server and storage components and establish connections to the same networks. The PRIMERGY BX Blade Servers are flexible and have complete control via a central administration instance that is redundant in design; they minimize administrative time and effort, freeing you of time-consuming administration tasks. Our build-to-order process ensures that only completely installed and previously tested solutions are supplied, which have been precisely adapted to individual requirements and which will grow with future business requirements.

PRIMERGY BX922 S2

The PRIMERGY BX922 S2 Server Blade uses up to two CPUs in the Intel® Xeon® processor 5000 sequence with up to 6 cores, including the first 32nm processors. Chipset and CPU offer comprehensive, hardware-based virtualization support which is supplemented by the additional functions on the new onboard Gigabit Ethernet Controller Intel® 82576. The main memory configuration with up to 12 DIMM modules rounds off the picture - the road is open for consolidation

strategies which are aligned with virtualization with hypervisor solutions from VMware, Microsoft, RedHat, Suse or Citrix. The design of the PRIMERGY BX922 S2 is very flexible regarding the boot options as - in addition to the increasing use of SAN or NAS - local booting via Solid State Disks and - especially for VMware ESXi - via a USB connected flash module is available. The efficient administration of the entire system via ServerView is supported by the integrated Remote Management Controller (iRMC S2); the hardware monitoring and setting options can thus be optimally visualized in order to use all options at the highest energy-efficiency levels.



Features and Benefits

Main Features	Benefits
<p>Performance due to processor technology</p> <ul style="list-style-type: none"> Two Dual-Core, Quad-Core or Six-Core CPUs with Intel® Xeon® processor 5500 and 5600 series with Turbo Boost technology, Demand Based Switching, QuickPath Interconnect (QPI) and internal Memory Management Unit. The Intel® QuickPath architecture memory controllers provide the BX922 S2 with a high-speed bandwidth of up to 25 Gigabytes/second (GB/s) between the individual processors, the processors and the memory, as well as between the processors and the I/O hub. <p>Top virtualization support</p> <ul style="list-style-type: none"> Two integrated dual-channel Intel® 82576 Gb Ethernet controllers are standard. The integrated Intel® virtualization technology for connectivity contains - in addition to I/O acceleration technology and the Virtual Machine Device Queues - Single Root IO virtualization SR-IOV as well. Two PCI Express 2.0 Mezzanine slots with a combination of quad-channel 1 Gb Ethernet, dual-channel 10Gb Ethernet, dual-channel 8 Gb Fibre Channel, dual-channel 10 Gb CNA (FCoE), and dual-channel 40 Gb Infiniband (QDR) offer excellent connection features via a high-performance midplane. The high server blade I/O capacity allows optimal use of various I/O protocols, ensuring smooth operations for demanding applications. <p>Flexible boot options</p> <ul style="list-style-type: none"> Various server boot options, e.g. from the network, from Hard Disk or Solid State Drives or from a USB Flash module (for VMware ESXi) make the server ideal for every application. It is an excellent platform for both virtualized and physical environments. <p>Worry-free administration</p> <ul style="list-style-type: none"> Management via the integrated Remote Management Controller (iRMC S2) enables access to each server and extensive control, even at remote locations. The integrated Pre-failure Detection and Analysis function provides reliable operations in all circumstances. 	<ul style="list-style-type: none"> Performance that can be tuned with constant energy consumption and heat dissipation. The optional use of two processor generations offers a choice for both the price-conscious user as well as the demanding high-performance user. Best-in-class I/O connectivity. High flexibility regarding the type of I/O connection. As a result of bypassing the internal hypervisor virtual switch SR-IOV enables virtual machines to reach a performance level which is almost the same as pure physical machines. Multiple use, optimized for virtualization and extremely energy efficient regarding usable local boot media. Easy and reliable management and control.

Technical details

Mainboard

Mainboard type	D 2861
Chipset	Intel® 5500
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5500 series / Intel® Xeon® processor E5600 series / Intel® Xeon® processor L5600 series / Intel® Xeon® processor X5600 series

Processor

Intel® Xeon® processor E5503 (2C/2T, 2.00 GHz, SLC: 4 x 256 KB, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)	
Intel® Xeon® processor E5603 (4C/4T, 1.60 GHz, SLC: -, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5606 (4C/4T, 2.13 GHz, SLC: -, TLC: 8 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5607 (4C/4T, 2.26 GHz, SLC: -, TLC: 8 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5620 (4C/8T, 2.40 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5640 (4C/8T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)	
Intel® Xeon® processor E5645 (6C/12T, 2.40 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 5.86 GT/s, Mem bus: 1333 MHz, 80 W)	
Intel® Xeon® processor E5649 (6C/12T, 2.53 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 5.86 GT/s, Mem bus: 1333 MHz, 80 W)	
Intel® Xeon® processor L5630 (4C/8T, 2.13 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 40 W)	
Intel® Xeon® processor L5640 (6C/12T, 2.26 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3/4/4, 6.4 GT/s, Mem bus: 1333 MHz, 60 W)	
Intel® Xeon® processor X5647 (4C/8T, 2.93 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 130 W)	
Intel® Xeon® processor X5650 (6C/12T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5660 (6C/12T, 2.80 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5667 (4C/8T, 3.06 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5675 (6C/12T, 3.06 GHz, SLC: -, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)	
Intel® Xeon® processor X5677 (4C/8T, 3.46 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)	
Intel® Xeon® processor X5687 (4C/8T, 3.60 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)	
Intel® Xeon® processor X5690 (6C/12T, 3.46 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)	
Memory slots	12 (3 channels per CPU with 2 slots each)
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	2 GB - 192 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Memory Mirroring support Hot-spare memory support

Memory Modules Independent Mode	2 GB (1 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
	2 GB (1 module(s) 2 GB) DDR3 LV, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Memory Modules Mirrored Mode	4 GB (2 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (2 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (2 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (2 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (2 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	32 GB (2 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Memory Modules Spare or Performance Mode	6 GB (3 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	12 GB (3 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	12 GB (3 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	24 GB (3 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	24 GB (3 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	48 GB (3 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Interfaces	
USB ports	4 x USB at the front via special cable
Graphics (15-pin)	1 x VGA at the front via special cable
Serial connection	1 x RS232 (9-pin) at the front via special cable
LAN / Ethernet (RJ-45)	4 x Gbit Ethernet via Midplane to Ethernet Connection Blade
Service LAN (RJ45)	Service LAN traffic can be switched to shared onboard Gbit LAN port
I/O controller on board	
RAID controller	RAID 0/1 for internal drives
SATA Controller	ICH10R
LAN Controller	2 x Intel® 82576, 4 x 10/100/1000 Mbit/s Ethernet, Intel® VT-c (includes I/OAT, VMDq, VMDc = PCI-SIG SR-IOV)
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / 1.2 (option)
Slots	
PCI-Express 2.0 x8	2 x BX900 Mezzanine Card
Storage drive bays	2 x 2.5-inch non hot-plug SATA HDD / 2.5-inch non hot-plug SATA SSD
Storage drive bay configuration	BX922 Disk Drive Mounting Kit needed for HDD/SSD support
Operating panel	
Operating buttons	On/off switch ID button
Status LEDs	Power (amber / green) System status (orange) LAN connection (green) Identification (blue) CSS (yellow)
BIOS	
BIOS features	Local and remote update via ServerView Update Manager Online update tools for main Windows and Linux versions SMBIOS V2.6 Remote PXE boot support Remote iSCSI boot support

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows HPC Server® 2008 R2 Suite
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	Microsoft® Windows® Server 2008 Datacenter
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Windows Server® 2003 Enterprise Edition
	Microsoft® Windows Server® 2003 Standard Edition
	VMware vSphere™ 5.0 Embedded
	VMware vSphere™ 5.0
	VMware vSphere™ 4.1
	VMware vSphere™ 4.1 Embedded
	VMware vSphere™ 4.1 Installable
	VMware vSphere™ 4.0
	VMware vSphere™ 4.0 Embedded
	VMware vSphere™ 4.0 Installable
	Novell® SUSE Linux Enterprise Server 11
	Novell® SUSE Linux Enterprise Server 10
	Novell® SUSE Linux Enterprise Server 10 with XEN
Red Hat® Enterprise Linux 6	
Red Hat® Enterprise Linux 5	
Red Hat® Enterprise Linux 5 with XEN	
Citrix® XenServer®	
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	<ul style="list-style-type: none"> ServerView Suite - Deploy <ul style="list-style-type: none"> SV Installation Manager SV Scripting Toolkit SV Deployment Manager (30-day trial version) ServerView Suite - Control <ul style="list-style-type: none"> SV Operations Manager incl. PDA and ASR & R (Prefailure and Analysis; Automatic Server Recovery and Restart) SV Performance Management SV Power Management SV RAID Manager ServerView Suite - Maintain <ul style="list-style-type: none"> SV Remote Management (iRMC) SV Update Management (BIOS, Firmware, Windows Drives and SV Agents) SV Asset Management SV Online Diagnostics ServerView Suite - Integrate <ul style="list-style-type: none"> SV Integration packs e.g. for Microsoft System Center, Nagios, HP, SIM, HP NNM, IBM Tivoli, Altiris Deployment Solutions and others
-----------------	---

Server Management

Option	ServerView Suite - Deploy SV Deployment Manager (full version) ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR) and Remote Storage ServerView Suite - Dynamize SV Virtual-IO Manager (VIOM) SV Resource Orchestrator Virtual Edition (ROR VE) SV Resource Orchestrator Cloud Edition (ROR CE) ServerView Suite - Integrate SV Integration pack for Fujitsu ManageNow® solution
Server Management notes	Regarding Operating System dependencies for ServerView Suite software products see dedicated product data sheets.

Dimensions / Weight

Dimensions (W x D x H)	45 x 500 x 210 mm
Weight	5,75 kg

Environmental

Temperature note	In accordance with the corresponding PRIMERGY BX900 System Unit
Operating environment	FTS 04230 Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473

Electrical values**Compliance**

Germany	GS
Europe	CE Class A *
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)

Compliance notes	In combination with corresponding PRIMERGY BX system unit There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
-------------------------	--

Compliance link	http://sp.ts.fujitsu.com/sites/certificates/
------------------------	---

Components

Storage disks	SSD SATA, 3 Gb/s, 64 GB, SLC, non hot plug, 2.5-inch, enterprise SSD SATA, 3 Gb/s, 32 GB, SLC, non hot plug, 2.5-inch, enterprise HDD SATA, 3 Gb/s, 320 GB, 5400 rpm, non hot plug, 2.5-inch, economic HDD SATA, 3 Gb/s, 160 GB, 5400 rpm, non hot plug, 2.5-inch, economic
----------------------	--

Mezzanine Cards	Ethernet Mezzanine Card 4 x 1 Gb Fujitsu , PCIe x4 CNA Mezzanine Card 2 x 10 Gb Emulex (MC-CNA102E), PCIe Gen2 x8 Ethernet Mezzanine Card 2 x 10 Gb Fujitsu , PCIe Gen2 x8 Fibre Channel Mezzanine Card 2 x 8 Gb Emulex (MC-FC82E), PCIe x4 InfiniBand CX2 Mezzanine Card 2 x 40 Gb Mellanox , PCIe x8 SAS HBA Mezzanine Card x 6 Gb Fujitsu (), PCIe Gen2 x8 SAS RAID Mezzanine Card x 6 Gb Fujitsu (), PCIe Gen2 x8
------------------------	---

Warranty

Standard Warranty	3 years
--------------------------	---------

Warranty

Service level (depending on country)

Maintenance and Support Services - the perfect extension

Recommended Service 7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.

Spare Parts availability 5 years

Service Weblink <http://www.fujitsu.com/fts/services>

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY BX922 S2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY BX922 S2, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/PRIMERGY>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU LIMITED

Website: www.fujitsu.com
2012-01-24 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions